

Stainless Steel Ball Valve - Pressfit Ends

LV 6306

Pressfit End Connections, 3 Piece CF8M Stainless Steel Body, ISO 5211 Direct Mount, Full Bore with Stainless Steel Lever and Plastic Cover.

Can be used with all tools with M-Contour; Mapress, Klauke, Rems, Rothenberger.



Pressure / Temperature Specifications	
Pressure	PN16
Temperature	-35°C to 135°C

Material Specifications					
1	Body	CF8M Stainless Steel	12	Handle	304 Stainless Steel
2	End	CF8M Stainless Steel	13	Handle Cover	Plastic
3	Ball	CF8M Stainless Steel	14	Stop	304 Stainless Steel
4	Seats	PTFE	15	Washer	304 Stainless Steel
5	Stem	304 Stainless Steel	16	Nut	304 Stainless Steel
6	Gland Nut	304 Stainless Steel	17	Washer	304 Stainless Steel
7	Washer	304 Stainless Steel	18	Nut	304 Stainless Steel
8	Gland Follower	304 Stainless Steel	19	Body Bolt	304 Stainless Steel
9	Stem Packing	PTFE	20	End Cap	316 Stainless Steel
10	Thrust Washer	PTFE	21	End Oring	EPDM
11	Stem Nut	304 Stainless Steel			

Dimensions															
Size	D	L	H	h	F	A	B	C	R1	R2	H1	W	Nm	Kg	
15mm	12.5	103	38.4	9	9	42	42	36	3	3	68.5	135	6.0	0.37	
18mm	15	106.5	42	9	9	42	42	36	3	3	72	135	6.0	0.5	
22mm	20	118	48	9	9	42	42	36	3	3	78	135	6.0	0.75	
28mm	25	134.5	55	11	11	50	50	42	3.5	3	90.5	152	10.0	1.08	
35mm	32	147	60	11	11	50	50	42	3.5	3	95.5	152	13.0	1.8	
42mm	38	160	70	14	14	70	70	50	4.5	3.5	107	188	19.0	2.4	

